

Setback Distances in feet
 Beltrami County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
48	120	180	230	280
72	50	70	90	110
77	50	80	100	120
116	130	210	270	330
117	150	230	300	360
121	60	80	110	130
125	50	60	70	90
147	60	90	120	140
167	60	90	120	140
191	160	250	340	400
202	130	210	290	350
205	130	210	280	350
243	50	70	80	90
272	150	190	220	250
280	140	240	300	330
404	50	80	90	110
432	110	200	220	240
439	130	180	200	220
481	130	240	260	280
482	150	210	240	270
514	200	250	270	290
534	200	250	300	350
540	50	70	80	90
541	200	250	300	350
543	50	110	200	290
544	50	70	90	110
545	50	70	90	110
546	50	70	80	90
547	170	270	360	400
549	200	250	300	350
560	200	250	300	300
561	50	70	120	140
563	90	130	150	180
565	130	210	240	270
582	50	70	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Beltrami County, Minnesota Table date: March 8, 2012

	607	70	110	130	160
616	50	50	60	70	
621	50	70	90	100	
624	80	130	180	220	
625	170	220	260	290	
627	50	100	190	280	
628	60	80	100	120	
653	50	70	90	110	
702	50	70	120	140	
712	150	260	360	400	
765	50	70	90	110	
799	50	70	80	90	
1804	60	80	100	130	
1807	50	70	90	110	
1808	50	110	200	290	
1878	60	90	110	130	
1922	50	80	90	110	
1923	50	60	80	90	
1924	150	210	240	270	
1925	130	210	240	270	
1935	150	260	350	400	
1939	90	130	150	180	
1959	60	80	100	120	
1991	50	70	80	90	
158B	120	190	250	300	
1993B	70	90	120	140	
199B	60	80	110	130	
240B	50	70	80	90	
242B	160	270	360	400	
267B	60	90	120	140	
328B	150	230	300	360	
32B	50	60	70	80	
32C	50	60	70	80	
458B	140	210	280	340	
496B	130	200	270	330	
505B	70	100	130	160	
620B	150	210	240	270	
626B	50	60	80	90	

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Beltrami County, Minnesota Table date: March 8, 2012

	150	180	210	240
709B	150	180	210	240
867B	150	220	280	330
B109A	50	70	80	90
B200A	50	80	100	120
B201A	50	80	90	110
B202A	50	70	90	110
B203A	90	130	150	180
B204A	50	70	90	110
B205A	50	100	150	170
B206A	60	90	110	130
B207A	140	240	300	330
B208A	150	210	240	270
B210A	130	210	240	270
B211A	50	100	150	170
C125	50	60	70	90
C158B	120	190	250	300
C1807	50	70	90	110
C1878	60	90	110	130
C240B	50	70	80	90
C243	50	70	80	90
C496B	130	200	270	330
C534	200	250	300	350
C540	50	70	80	90
C544	50	70	90	110
C546	50	70	80	90
C549	200	250	300	300
C561	50	70	120	140
C620B	150	210	240	270
C628	60	80	100	120
C799	50	70	80	90
C867B	150	220	280	330
H87	50	60	80	90
H88	50	60	80	90
I12A	130	210	240	270
I27A	60	90	110	130
I38A	130	240	260	280
I45A	90	130	150	180
I50A	60	80	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Beltrami County, Minnesota Table date: March 8, 2012

I53A	50	70	90	110
I59A	50	70	90	110
I60A	50	70	90	110
I61A	110	200	220	240
I71A	50	100	150	170
I72A	140	240	300	330
I8A	50	70	90	110
J11	50	70	80	90
J5	120	190	250	310
J6	150	220	280	330
J7	50	70	80	90
N80	150	210	240	270
O92	120	180	230	280
O94	130	210	270	330

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.