

Setback Distances in feet
Marshall County, Minnesota Table date: February 3, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
47	60	90	110	130
58	60	90	110	130
59	150	210	230	250
65	160	210	230	250
77	50	80	100	120
111	140	220	280	350
116	130	210	270	330
117	150	230	300	360
145	130	210	230	250
148	130	200	250	310
187	60	110	140	160
205	130	210	280	350
236	50	70	90	100
280	140	240	300	330
372	130	210	270	340
383	60	90	110	140
384	60	90	110	140
387	50	70	90	110
412	150	240	330	350
418	70	110	140	170
426	150	210	230	250
432	110	200	220	240
435	100	150	190	230
439	140	190	210	230
481	130	240	260	280
482	150	210	240	270
514	200	250	270	290
540	50	70	80	90
541	200	250	300	350
543	50	110	200	290
544	50	70	90	110
546	50	70	80	90
547	170	270	360	400
550	70	100	120	140
563	90	130	150	180

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Marshall County, Minnesota Table date: February 3, 2012

565	130	210	240	270
582	50	70	90	110
583	50	70	90	110
641	50	80	100	120
642	60	90	110	130
643	150	210	230	260
644	50	80	100	120
645	150	210	230	260
647	150	210	230	260
648	50	80	100	110
649	60	80	90	110
650	60	80	90	110
651	140	210	230	250
652	200	250	270	290
653	50	70	90	110
708	160	270	360	400
712	150	260	360	400
713	130	190	210	230
765	50	70	90	110
794	150	260	360	400
935	50	60	80	90
936	50	80	110	130
937	60	90	120	140
972	50	70	90	110
1031	50	70	80	90
1144	140	190	210	230
1146	90	130	150	180
1158	70	100	140	160
1170	70	100	140	160
1187	70	100	120	140
1188	60	80	100	110
1189	50	80	100	130
1191	170	260	360	400
1264	130	200	260	330
1297	160	250	270	290
1804	60	80	100	130
1807	50	70	90	110
1808	50	110	200	290

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Marshall County, Minnesota Table date: February 3, 2012

1871	50	60	80	90
1874	160	270	360	400
1878	60	90	110	130
1963	50	80	100	120
1964	50	80	100	120
1966	140	230	300	370
1304B	90	130	170	210
1315A	130	200	220	240
157A	50	70	90	110
157B	50	70	90	110
184A	50	70	90	110
242B	160	270	360	400
258B	150	250	340	400
429A	60	90	120	140
57A	50	50	70	90
67A	60	90	110	130
67B	60	90	110	130
93A	60	90	110	130

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.