

Setback Distances in feet
 Rice County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
17	100	160	220	260
24	50	50	60	70
44	60	100	140	170
98	50	80	100	120
109	50	60	70	80
113	50	60	80	90
114	50	60	80	100
130	50	80	90	110
134	50	60	80	100
176	60	90	110	140
208	120	230	310	400
219	50	60	70	90
239	50	60	70	90
253	50	60	80	90
256	50	70	90	100
307	50	50	70	80
323	50	80	100	110
377	50	70	90	100
378	50	50	60	70
392	120	240	340	400
414	50	60	70	80
523	50	70	80	90
525	50	70	140	170
548	50	150	240	380
757	60	80	90	110
761	50	70	90	100
764	50	70	160	190
1016	60	90	100	120
1058	50	70	80	90
1080	50	70	110	120
1286	60	80	100	120
1360	80	180	260	330
1361	50	70	90	110
1363	50	60	70	80
1366	100	190	260	320

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Rice County, Minnesota Table date: March 8, 2012

	50	50	60	70
1367	50	50	60	70
1501	50	70	130	150
1831	70	100	120	140
1962	50	70	90	100
102B	50	70	90	110
104B	50	50	70	80
104C2	50	50	70	80
106C2	50	60	80	90
1362B	50	50	70	80
1387A	50	70	90	110
1388B	50	60	80	90
138B	50	80	100	120
138C	50	80	100	120
1408B	50	50	60	70
1409A	50	50	60	70
1409B	50	60	70	80
1410B	50	50	70	80
1410C	50	50	70	80
1413B	70	100	130	140
1416C	50	60	70	80
1437B	50	60	70	80
213B	50	70	80	90
238B	60	90	110	130
238C2	60	90	110	130
285A	70	110	140	170
285B	70	110	140	170
301B	80	120	160	170
301C	80	120	160	170
376B	50	70	90	100
382B	60	80	100	120
382C2	60	80	100	120
39A	150	290	400	400
411A	140	260	380	400
411B	140	260	380	400
41A	140	230	300	380
41B	140	230	300	380
463A	90	150	200	250
528B	50	70	120	140

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Rice County, Minnesota Table date: March 8, 2012

	74B	90	150	200	250
783C2	50	60	80	90	
875B	130	230	300	370	
875C	130	230	300	370	
945C2	50	60	80	90	
963C2	70	100	140	160	

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.