


# CORNER BRACE ASSEMBLY



## POSTS

ALL WOOD POSTS EXCEPT RED CEDAR, BLACK LOCUST, TAMARACK, WHITE CEDAR, REDWOOD, WHITE OAK, AND BURR OAK SHALL BE TREATED BY A METHOD SUCH THAT COMPLETE SATURATION OF THE SAPWOOD IS OBTAINED.

USED RAILROAD TIES OR HIGHLINE POLES IN SOUND CONDITION MAY BE UTILIZED FOR POSTS IF FREE FROM CRACKING OR DECAY.

## BRACE WIRE

2 COMPLETE LOOPS OF 9 Ga. WIRE OR 1 COMPLETE LOOP OF 12.5 Ga. HIGH TENSILE WIRE.

ALL WIRE SHALL HAVE A SUFFICIENT COATING TO PROTECT THE WIRE FOR THE MINIMUM LIFE EXPECTANCY OF 20 YEARS.

**CORNERS ARE REQUIRED AT ALL POINTS WHERE THE FENCE ALIGNMENT CHANGES 15 DEGREES OR MORE.**

PRACTICE MEETS MN NRCS STANDARDS AND SPECIFICATIONS

YES \_\_\_\_\_ NO \_\_\_\_\_

CERTIFIED BY:

\_\_\_\_\_  
Name and Date

MN-ECS-020  
5-06