


**END PANEL, CORNER, GATE, AND DIRECTION CHANGE ASSEMBLY**

**MATERIALS NOTES**

1. ALL MATERIALS SHALL BE SOUND, NEW, AND FREE OF DECAY AND RUST.
2. TREATED POSTS SHALL BE COMMERCIALY AVAILABLE PRESSURE TREATED.
3. STEEL LINE POSTS SHALL BE 'TEE' TYPE WITH SUITABLE APPURTENCES FOR FASTENING LINE WIRES AND SHALL HAVE AN ATTACHED ANCHOR PLATE. STEEL POSTS WILL BE PAINTED OR GALVANIZED AND HAVE A MINIMUM WEIGHT OF 1.33 POUNDS PER FOOT EXCLUSIVE OF ANCHOR PLATE.
4. BARBED WIRE SHALL BE TWO TWISTED STRANDS OF 12 1/2 GAUGE OR HEAVIER WIRE WITH 14 GAUGE OR HEAVIER TWO POINT BARBS ON APPROXIMATELY 4 INCH CENTERS. ZINC COATING IS REQUIRED.
5. WOVEN WIRE SHALL BE AT LEAST 32 INCHES HIGH WITH 11 GAUGE OR HEAVIER TOP AND BOTTOM WIRES. LINE AND STAY WIRES SHALL BE 14 1/2 GAUGE OR HEAVIER. ZINC COATING IS REQUIRED.

**CONSTRUCTION NOTES**

1. CORNER, END, BRACE, AND PULL POSTS SHALL BE LOCATED AND SET FIRST.
2. STEEL POSTS SHALL BE USED AT LEAST EVERY 100 FEET FOR GROUNDING PURPOSES. STEEL POSTS MAY BE USED IN LINE CONSTRUCTION. LENGTH OF STEEL POSTS SHALL BE 6 FEET SET TO A DEPTH OF 2 FEET OR AT LEAST ONE INCH OVER THE ANCHOR PLATE, WHICH EVER IS GREATER.
3. LOCATION AND TYPE OF GATES ARE TO BE DETERMINED BY OWNER.
4. CUT NOTCH INTO GATE, BRACE, AND CORNER POSTS FOR HORIZONTAL BRACE. HORIZONTAL BRACE SHOULD BE PLACED APPROXIMATELY 3 FEET ABOVE GROUND.
5. STAPLE NO. 9 CROSS-BRACE, AND FENCE WIRES TO GATE, BRACE AND CORNER POSTS AT QUARTER POINTS OF POSTS.
6. FOR ADDED SAFETY, 2 STRANDS OF BARBED WIRE MAY BE INSTALLED ABOVE WOVEN WIRE ON 6 INCH SPACINGS.



**LINE FENCE SECTION**

DATE	
DESIGNED	
DRAWN	
CHECKED	
APPROVED	

WOVEN WIRE MESH SAFETY FENCE



File No.  
MN610.DWG  
Drawing No.  
MN-ENG-510  
5/02

REVISIONS	
NO.	DATE

Sheet of